

Report No.: T200117D02-D

Ref No.: T131217D02-D

Page: 1 / 29
Rev.: 01

FCC TEST REPORT

for

Motherboard

MODEL: IMB-150D; IMB-150M; IMB-150N; 261D; 261M; IMBXXXXXXXXXX;
IMB-150XXXXXX(X="0-9","A-Z","a-z","+","-","(",")","/","blank")

Issued to:

ASRock Industrial Computer Corporation

7F., No.9, Ln. 79, Ligong St., Beitou Dist.,
Taipei City 11261, Taiwan (R.O.C.)

Issued by:

Compliance Certification Services Inc.**Xindian Lab.**

No.163-1, Jhongsheng Rd., Xindian Dist.,
New Taipei City, 23151 Taiwan.

TEL: 886-2-22170894

FAX: 886-2-22171029

Issued Date: January 20, 2020

Note: This document may be altered or revised by Compliance Certification Services Inc. personnel only, and shall be noted in the revision section of the document. The client should not use it to claim product endorsement by TAF, A2LA, NIST or any government agencies.

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部分複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms_and_conditions.htm and for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms_e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.



Report No.: T200117D02-D

Ref No.: T131217D02-D

Page: 2 / 29
Rev.: 01

Revision History

Rev.	Issue Date	Revisions	Effect Page	Revised By
00	December 27, 2013	Initial Issue	ALL	Wendy Wang
01	January 20, 2020	Update Standards & add model	ALL	Wendy Wang



Report No.: T200117D02-D

Ref No.: T131217D02-D

Page: 3 / 29
Rev.: 01

TABLE OF CONTENTS

1	TEST RESULT CERTIFICATION	4
2	EUT DESCRIPTION	5
3	TEST METHODOLOGY	6
3.1.	DECISION OF FINAL TEST MODE	6
3.2.	EUT SYSTEM OPERATION	6
4	SETUP OF EQUIPMENT UNDER TEST	7
4.1.	DESCRIPTION OF SUPPORT UNITS	7
4.2.	CONFIGURATION OF SYSTEM UNDER TEST	8
5	FACILITIES AND ACCREDITATIONS	9
5.1.	FACILITIES	9
5.2.	ACCREDITATIONS	9
5.3.	MEASUREMENT UNCERTAINTY	9
6	CONDUCTED EMISSION MEASUREMENT	10
6.1.	LIMITS OF CONDUCTED EMISSION MEASUREMENT	10
6.2.	TEST INSTRUMENTS	10
6.3.	TEST PROCEDURES	11
6.4.	TEST SETUP	12
6.5.	DATA SAMPLE	12
6.6.	TEST RESULTS	13
7	RADIATED EMISSION MEASUREMENT	15
7.1.	LIMITS OF RADIATED EMISSION MEASUREMENT	15
7.2.	TEST INSTRUMENTS	17
7.3.	TEST PROCEDURES	18
7.4.	TEST SETUP	19
7.5.	DATA SAMPLE	20
7.6.	TEST RESULTS	21
8	PHOTOGRAPHS OF THE TEST CONFIGURATION	27
	APPENDIX 1 - PHOTOGRAPHS OF EUT	A1-1

1 TEST RESULT CERTIFICATION

Product: Motherboard

Model: IMB-150D; IMB-150M; IMB-150N; 261D; 261M; IMBXXXXXXXXXX;
IMB-150XXXXXX(X="0-9","A-Z","a-z","+","-","(",")","/","blank")

Brand: 

Applicant: **ASRock Industrial Computer Corporation**
7F., No.9, Ln. 79, Ligong St., Beitou Dist.,
Taipei City 11261, Taiwan (R.O.C.)

Manufacturer: **ASRock Industrial Computer Corporation**
7F., No.9, Ln. 79, Ligong St., Beitou Dist.,
Taipei City 11261, Taiwan (R.O.C.)

Tested: December 18, 2013 & December 25, 2013


EMISSION			
Standard	Item	Result	Remarks
FCC 47 CFR Part 15 Subpart B, ICES-003 Issue 6-2016 ANSI C63.4-2014	Conducted (Power Port)	PASS	Meet Class B limit
	Radiated	PASS	Meet Class B limit

Statements of Conformity

Determination of compliance is based on the results of the compliance measurement, not taking into account measurement instrumentation uncertainty.

The above equipment has been tested by Compliance Certification Services Inc., and found compliance with the requirements set forth in the technical standards mentioned above. The results of testing in this report apply only to the product/system, which was tested. Other similar equipment will not necessarily produce the same results due to production tolerance and measurement uncertainties.

Approved by:



Sam Hu
Assistant Manager

Reviewed by:



Eva Fan
Supervisor of report document dept.

2 EUT DESCRIPTION

Product	Motherboard
Brand Name	
Model	IMB-150D; IMB-150M; IMB-150N; 261D; 261M; IMBXXXXXXXXX; IMB-150XXXXXX(X="0-9","A-Z","a-z","+","-","(",")","/","blank")
Applicant	ASRock Industrial Computer Corporation
Housing material	N/A
Identify Number	T131217D02
Received Date	December 17, 2013
EUT Power Rating	3.3VDC/ ± 5 VDC/ ± 12 VDC from Host PC Power Supply
AC Power During Test	120VAC / 60Hz to Host PC Power Supply

Model Difference

Model Name	Difference	Tested (Checked)
IMB-150D	Original	☒
IMB-150M; IMB-150N; 261D; 261M; IMBXXXXXXXXX; IMB-150XXXXXX	1. X="0-9","A-Z","a-z","+","-","(",")","/","blank" 2. For marketing purpose only.	☐

I/O PORT

I/O PORT TYPES	Q'TY	TESTED WITH
1. PIO Port	1	1
2. PS/2 Keyboard Port	1	1
3. PS/2 Mouse Port	1	1
4. VGA Port	1	1
5. Earphone Port	1	1
6. Microphone Port	1	1
7. USB 2.0 Port	6	6
8. LAN Port	2	2
9. USB 3.0 Port	4	4
10. SIO Port	5	5
11. HDMI Port	1	1

Note: Client consigns only one model sample to test (Model Number: IMB-150D).

3 TEST METHODOLOGY

3.1. DECISION OF FINAL TEST MODE

The EUT was tested together with the below additional components, and a configuration, which produced the worst emission levels, was selected and recorded in this report.

The test configuration/ modes are as the following:

Conduction Modes:

No.	CPU	Operate State	
1	Intel / J1900 (2.0GHz)	D-SUB + HDMI Mode	1920X1200, VF=60Hz
2			1600X1200, VF=60Hz
3			1280X1024, VF=60Hz
4			800X600, VF=60Hz
5	Intel / N2920 (1.86GHz)		1920X1200, VF=60Hz

Radiation Modes:

No.	CPU	Operate State	
1	Intel / J1900 (2.0GHz)	D-SUB + HDMI Mode	1920X1200, VF=60Hz
			1920X1200, VF=60Hz / Open Chassis
			1920X1200, VF=60Hz / 1-10GHz
			1920X1200, VF=60Hz / 1-10GHz / Open Chassis
2			1600X1200, VF=60Hz
3			1280X1024, VF=60Hz
4			800X600, VF=60Hz
5	Intel / N2920 (1.86GHz)		1920X1200, VF=60Hz

Conduction: Mode 1

Radiation: Mode 1

3.2. EUT SYSTEM OPERATION

1. Windows 8 boots system.
2. Run Emctest.exe to activate all peripherals and display "H" pattern on monitor screen.
3. Run Winemc.exe and choose "E:/ & F:/" to test USB 2.0 ports.
4. Run Winemc.exe and choose "G:/ & H:/ & I:/ & J:/" to test USB 3.0 ports.
5. Press the start menu, select executive and type ping 192.168.1.10 -t (EUT), ping 192.168.1.20 -t (Server PC).
6. Press the start menu, select executive and type ping 192.168.0.10 -t (EUT), ping 192.168.10.20 -t (Server PC).

Note: Test program is self-repeating throughout the test.

4 SETUP OF EQUIPMENT UNDER TEST

4.1. DESCRIPTION OF SUPPORT UNITS

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

Host PC Devices:

No	Equipment	Model #	Serial #	FCC ID/ BSMI ID	Brand Name
1.	HDD	ST340016A	3HR0ZMB9	BSMI ID: 3902B322 BSMI: D33016	Seagate
2.	Power supply	SS-500FB Active PFC	N/A	BSMI: D33080 DoC	Seasonic
3.	CD/R	CD-552E	5145319	BSMI: D33066 DoC	TEAC
4.	CPU FC-BGA 1170 (1.86GHz)	N2920	N/A	N/A	INTEL
	CPU FC-BGA 1170 (2.0GHz)	J1900	N/A	N/A	INTEL
5	SODIMM (DDRIII1333)	N/A	N/A	N/A	NANYA
6	SATA3 HDD	WD6402AAEX	N/A	N/A	WD


Peripherals Devices:

No.	Equipment	Model No.	Serial No.	FCC ID / BSMI ID	Brand Name	Data Cable	Power Cord
1-2	USB 2.0 HDD	F12-U	N/A	BSMI ID: 4912A002	TeraSys	Shielded, 1.8m	N/A
3	Earphone & Microphone	MSB301	N/A	N/A	e-Sense	Unshielded, 1.8m	N/A
4-7	USB Mouse	M-BE58	N/A	DOC BSMI: T41126	Logitech	Shielded, 1.8m	N/A
8	PS/2 Mouse	M-SBF96	FATSQ0C5BYJQKZ	DOC BSMI: R41126	hp	Shielded, 1.8m	N/A
9	PS/2 Keyboard	SK-2880	BAUEL0HCPY76G7	DOC BSMI: T3A002	hp	Shielded, 1.8m	N/A
10-14	Modem	AL-56ERM	0MERM04A0212	DOC	GALILEO	Shielded, 1.5m	Unshielded, 1.8m
15-16	USB 3.0 HDD	NU6020	N/A	N/A	GOOD WAY	Shielded, 1.5m	N/A
17-18	USB 3.0 HDD	NU6020	N/A	N/A	GOOD WAY	Shielded, 1.5m	N/A
19	Printer	C60	DR3K039417	BSMI ID: 3902E006	EPSON	Shielded, 1.8m	Unshielded, 1.8m
20	Monitor	U2412MD	N/A	DOC BSMI: R33002	DELL	Shielded, 1.8m	Unshielded, 1.8m
21	Monitor	U2713MHt	N/A	DOC BSMI: R33002	DELL	Shielded, 1.5m with two cores	Unshielded, 1.8m
22	Server PC	T3500	8X36VBX	DOC BSMI: R33002	DELL	Unshielded, 20m	Unshielded, 1.8m
23	Server PC	T3500	9X36VBX	DOC BSMI: R33002	DELL	Unshielded, 20m	Unshielded, 1.8m

Note:

- 1) All the equipment/cables were placed in the worst-case configuration to maximize the emission during the test.
- 2) Grounding was established in accordance with the manufacturer's requirements and conditions for the intended use.

4.2. CONFIGURATION OF SYSTEM UNDER TEST



5 FACILITIES AND ACCREDITATIONS

5.1. FACILITIES

All measurement facilities used to collect the measurement data are located at CCSrf Taiwan Xindian Lab. at No.163-1, Jhongsheng Rd., Xindian Dist., New Taipei City, 23151 Taiwan.

The sites are constructed in conformance with the requirements of ANSI C63.4 and CISPR Publication 22. All receiving equipment conforms to CISPR 16-1-1, CISPR 16-1-2, CISPR 16-1-3, CISPR 16-1-4 and CISPR 16-1-5.

5.2. ACCREDITATIONS

Our laboratories are accredited and approved by the following accreditation body according to ISO/IEC 17025.

Taiwan	TAF
USA	A2LA

The measuring facility of laboratories has been authorized or registered by the following approval agencies.

Canada	Industry Canada
Japan	VCCI
Taiwan	BSMI
USA	FCC

Copies of granted accreditation certificates are available for downloading from our web site, <http://www.ccsrf.com>

5.3. MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2:

Measurement	Frequency	Uncertainty
Conducted emissions	0.15MHz ~ 30MHz	± 1.56
Radiated emissions	30MHz ~ 1000MHz	± 3.91
	1000MHz ~ 18000MHz	± 3.23
	18000MHz ~ 26000MHz	± 3.07
	26000MHz ~ 40000MHz	± 3.42

This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.

Consistent with industry standard (e.g. CISPR 22: 2005, clause 11, Measurement Uncertainty) determining compliance with the limits shall be base on the results of the compliance measurement. Consequently the measure emissions being less than the maximum allowed emission result in this be a compliant test or passing test.

The acceptable measurement uncertainty value without requiring revision of the compliance statement is base on conducted and radiated emissions being less than UCISPR which is 3.4dB(AMN) and 6.3dB(OATS) respectively. CCS values (called ULab in CISPR 16-4-2) is less than UCISPR as shown in the table above. Therefore, MU need not be considered for compliance.

6 CONDUCTED EMISSION MEASUREMENT

6.1. LIMITS OF CONDUCTED EMISSION MEASUREMENT

FREQUENCY (MHz)	Class A (dBUV)		Class B (dBUV)	
	Quasi-peak	Average	Quasi-peak	Average
0.15 - 0.5	79	66	66 - 56	56 - 46
0.50 - 5.0	73	60	56	46
5.0 - 30.0	73	60	60	50

NOTE:

- (1) The lower limit shall apply at the transition frequencies.
- (2) The limit decreases in line with the logarithm of the frequency in the range 0.15 to 0.50 MHz.
- (3) All emanations from a class A/B digital device or system, including any network of conductors and apparatus connected thereto, shall not exceed the level of field strengths specified above.

6.2. TEST INSTRUMENTS

Conducted Emission room # B				
Name of Equipment	Manufacturer	Model	Serial Number	Calibration Due
TEST RECEIVER	R&S	ESCI	100234	06/10/2014
LISN (EUT)	FCC	FCC-LISN-50-32-2	08009	03/25/2014
LISN	SCHWARZBECK	NSLK 8127	8127382	01/07/2014
BNC CABLE	EMCI	CFD300-NL	BNC B4	03/14/2014
Pulse Limiter	R&S	ESH3-Z2	100374	01/09/2014
THERMO-HYGRO METER	WISEWIND	201A	No. 05	06/10/2014
Test S/W	EZ-EMC			

- NOTE:** 1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.
2. N.C.R = No Calibration Request.

6.3. TEST PROCEDURES (please refer to measurement standard or CCS SOP PA-031)


Procedure of Preliminary Test

- The EUT and support equipment, if needed, were set up as per the test configuration to simulate typical usage per the user's manual. When the EUT is a tabletop system, a wooden table with a height of 0.8 meters is used and is placed on the ground plane as per ANSI C63.4 (see Test Facility for the dimensions of the ground plane used). When the EUT is a floor standing equipment, it is placed on the ground plane, which has a 12 mm non-conductive covering to insulate the EUT from the ground plane.
- All I/O cables were positioned to simulate typical actual usage as per ANSI C63.4.
- The test equipment EUT installed by AC 120VAC/60Hz main power, through a Line Impedance Stabilization Network (LISN), which was supplied power source and was grounded to the ground plane.
- All support equipment power by from a second LISN.
- The test program of the EUT was started. Emissions were measured on each current carrying line of the EUT using an EMI Test Receiver connected to the LISN powering the EUT.
- The Receiver scanned from 150kHz to 30MHz for emissions in each of the test modes.
- During the above scans, the emissions were maximized by cable manipulation.
- The test mode(s) described in Item 3.1 were scanned during the preliminary test.
- After the preliminary scan, we found the test mode described in Item 3.1 producing the highest emission level.
- The worst configuration of EUT and cable of the above highest emission level were recorded for reference of the final test.

Procedure of Final Test

- EUT and support equipment were set up on the test bench as per the configuration with highest emission level in the preliminary test.
- A scan was taken on both power lines, Line 1 and Line 2, recording at least the six highest emissions. Emission frequency and amplitude were recorded into a computer in which correction factors were used to calculate the emission level and compare reading to the applicable limit.
- The test data of the worst-case condition(s) was recorded.

6.4. TEST SETUP



- For the actual test configuration, please refer to the related item – Photographs of the Test Configuration.

6.5. DATA SAMPLE

Freq. (MHz)	Reading (dBuV)	Factor (dB)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Detector (P/Q/A)	Line (L1/L2)
x.xx	42.95	0.55	43.50	56	-12.50	Q	L1


Freq. = Emission frequency in MHz
 Reading = Uncorrected Analyzer/Receiver reading
 Factor = Insertion loss of LISN + Cable Loss + Pulse Limit
 Result = Reading + Factor
 Limit = Limit stated in standard
 Margin = Reading in reference to limit
 P = Peak Reading
 Q = Quasi-peak Reading
 A = Average Reading
 L1 = Hot side
 L2 = Neutral side

Calculation Formula

Margin (dB) = Result (dBuV) – Limit (dBuV)

6.6. TEST RESULTS


Model No.	IMB-150D	6dB Bandwidth	9 kHz
Environmental Conditions	24°C, 60% RH	Test Mode	Mode 1
Tested by	Kirin Ho	Phase	L1
Standard	FCC CLASS B		



Conducted Emission Readings							
Frequency Range Investigated				150 kHz to 30 MHz			
Freq. (MHz)	Reading (dBuV)	Factor (dB)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Detector (P/Q/A)	Line (L1/L2)
0.1980	39.84	9.87	49.71	63.69	-13.98	P	L1
0.2620	27.49	9.88	37.37	61.36	-23.99	P	L1
0.7140	27.01	9.94	36.95	56.00	-19.05	P	L1
1.2260	27.05	10.00	37.05	56.00	-18.95	P	L1
2.5500	27.23	10.09	37.32	56.00	-18.68	P	L1
3.5700	32.17	10.13	42.30	56.00	-13.70	P	L1
10.6019	32.56	10.29	42.85	60.00	-17.15	P	L1
21.9140	31.19	10.57	41.76	60.00	-18.24	P	L1

Note: 1. L1 = Line One (Live Line) / L2 = Line Two (Neutral Line).

Model No.	IMB-150D	6dB Bandwidth	9 kHz
Environmental Conditions	24°C, 60% RH	Test Mode	Mode 1
Tested by	Kirin Ho	Phase	L2
Standard	FCC CLASS B		



Conducted Emission Readings							
Frequency Range Investigated				150 kHz to 30 MHz			
Freq. (MHz)	Reading (dBuV)	Factor (dB)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Detector (P/Q/A)	Line (L1/L2)
0.1980	37.70	9.88	47.58	63.69	-16.11	P	L2
0.2620	26.92	9.89	36.81	61.36	-24.55	P	L2
0.6140	27.08	9.93	37.01	56.00	-18.99	P	L2
0.7140	27.88	9.95	37.83	56.00	-18.17	P	L2
1.2260	27.18	10.00	37.18	56.00	-18.82	P	L2
2.5500	27.18	10.09	37.27	56.00	-18.73	P	L2
3.5700	33.19	10.13	43.32	56.00	-12.68	P	L2
10.6020	32.64	10.29	42.93	60.00	-17.07	P	L2
21.5020	31.58	10.55	42.13	60.00	-17.87	P	L2

Note: 1. L1 = Line One (Live Line) / L2 = Line Two (Neutral Line).

7 RADIATED EMISSION MEASUREMENT

7.1. LIMITS OF RADIATED EMISSION MEASUREMENT

Below 1GHz (for digital device)

FREQUENCY (MHz)	dBuV/m (At 10m)	
	Class A	Class B
30 ~ 230	40	30
230 ~ 1000	47	37

Limit tables for non-digital device:

Class A Radiated Emission limit at 10m (for others)

Frequency (MHz)	Field Strength Limit (uV/m)Q.P.	Field Strength Limit (dBuV/m)Q.P.
30 - 88	90	39
88 - 216	150	43.5
216 – 960	210	46.4
Above 960	300	49.5

Class B Radiated Emission limit at 3m (for others)

Frequency (MHz)	Field Strength Limit (uV/m)Q.P.	Field Strength Limit (dBuV/m)Q.P.
30 - 88	100	40
88 - 216	150	43.5
216 – 960	200	46
Above 960	500	54

Above 1GHz(for all device)

Frequency (MHz)	Class A (dBuV/m) (At 10m)		Class B (dBuV/m) (At 3m)	
	Average	Peak	Average	Peak
Above 1000	49.5	69.5	54	74

NOTE: (1) The lower limit shall apply at the transition frequencies.

(2) Emission level (dBuV/m) = 20 log Emission level (uV/m).

(3) The measurement above 1GHz is at close-in distances 3m, and determine the limit **L2** corresponding to the close-in distance **d2** by applying the following relation: **L2 = L1 (d1/d2)**, where **L1** is the specified limit in microvolts per metre (uV/m) at the distance **d1 (10m)**, **L2** is the new limit for distance **d2 (3m)**.

So the new Class A limit above 1GHz at 3m is as following table:

Frequency (MHz)	Class A (dBuV/m) (At 3m)	
	Average	Peak
Above 1000	60	80

According to FCC Part 15.33 (b), for an unintentional radiator, including a digital device, the spectrum shall be investigated from the lowest radio frequency signal generated or used in the device, without going below the lowest frequency for which a radiated emission limit is specified, up to the frequency shown in the following table:

Highest frequency generated or used in the device or on which the device operates or tunes (MHz)	Upper frequency of measurement range (MHz)
Below 1.705	30
1.705-108	1000
108-500	2000
500-1000	5000
Above 1000	5 th harmonic of the highest frequency or 40GHz, whichever is lower

7.2. TEST INSTRUMENTS

Open Area Test Site # J				
Name of Equipment	Manufacturer	Model	Serial Number	Calibration Due
MEASURE RECEIVER	R&S	ESCI	101054	04/07/2014
ANTENNA	SUNOL	JB1	A100209-2	09/08/2014
PRE-AMPLIFIER	SCHAFFNER	CPA9231A	3613	05/30/2014
CABLE	EMCI	8Dr	N-TYPE #J4、J6	08/15/2014
THERMO-HYGRO METER	WISEWIND	201A	No. 04	06/10/2014
Test S/W	EZ-EMC			
Above 1GHz Used				
SPECTRUM ANALYZER (9kHz-30GHz)	R&S	FSP 30	100112	10/22/2014
ANTENNA (1-18GHz)	ETS	3117	00139062	10/31/2014
AMPLIFIER (1-26.5GHz)	HP	8449B	3008A01266	12/15/2014
CABLE (1-40GHz)	HUBER +SUHNER	SUCOFLEX 102	33106/2	12/15/2014
CABLE (1-40GHz)	HUBER +SUHNER	SUCOFLEX 102	33633/2	12/15/2014
CABLE (1-26.5GHz)	HUBER +SUHNER	SUCOFLEX 104PEA	33960/4PEA	12/15/2014
THERMO-HYGRO METER	WISEWIND	201A	No. 02	05/14/2014
Test S/W	EZ-EMC			

NOTE: 1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.
 2. N.C.R = No Calibration Request.

7.3. TEST PROCEDURES (please refer to measurement standard or CCS SOP PA-031)

Procedure of Preliminary Test


- The equipment was set up as per the test configuration to simulate typical usage per the user's manual. When the EUT is a tabletop system, a wooden turntable with a height of 0.8 meters is used which is placed on the ground plane. When the EUT is a floor standing equipment, it is placed on the ground plane which has a 12 mm non-conductive covering to insulate the EUT from the ground plane.
- Support equipment, if needed, was placed as per ANSI C63.4.
- All I/O cables were positioned to simulate typical usage as per ANSI C63.4.
- The EUT received AC 120VAC/60Hz power source from the outlet socket under the turntable. All support equipment power received from another socket under the turntable.
- The antenna was placed at 3 or 10 meter away from the EUT as stated in ANSI C63.4. The antenna connected to the Spectrum Analyzer via a cable and at times a pre-amplifier would be used.
- The Analyzer / Receiver quickly scanned from 30MHz to 40GHz. The EUT test program was started. Emissions were scanned and measured rotating the EUT to 360 degrees and positioning the antenna 1 to 4 meters above the ground plane, in both the vertical and the horizontal polarization, to maximize the emission reading level.
- The test mode(s) described in Item 3.1 were scanned during the preliminary test:
- After the preliminary scan, we found the test mode described in Item 3.1 producing the highest emission level.
- The worst configuration of EUT and cable of the above highest emission level were recorded for reference of the final test.

Procedure of Final Test


- EUT and support equipment were set up on the turntable as per the configuration with highest emission level in the preliminary test.
- The Analyzer / Receiver scanned from 30MHz to 40GHz. Emissions were scanned and measured rotating the EUT to 360 degrees, varying cable placement and positioning the antenna 1 or 1 to 4 meters above the ground plane, in both the vertical and the horizontal polarization, to maximize the emission reading level.
- Recording at least the six highest emissions. Emission frequency, amplitude, antenna position, polarization and turntable position were recorded into a computer in which correction factors were used to calculate the emission level and compare reading to the applicable limit. Below 1GHz the Q.P. reading and above 1GHz the Peak and Average reading are presented.
- The test data of the worst-case condition(s) was recorded.

7.4. TEST SETUP

Below 1GHz



Above 1GHz



- For the actual test configuration, please refer to the related item – Photographs of the Test Configuration.

7.5. DATA SAMPLE

Below 1GHz

Freq. (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector (P/Q)	Pol. (H/V)
x.xx	14.0	12.2	26.2	30	-3.8	Q	H

Above 1GHz

Freq. (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector (P/A)	Pol. (H/V)
x.xx	42.95	0.55	43.50	54	-10.50	A	H

Freq. = Emission frequency in MHz
 Reading = Uncorrected Analyzer/Receiver reading
 Factor = Antenna Factor + Cable Loss - Amplifier Gain
 Result = Reading + Factor
 Limit = Limit stated in standard
 Margin = Reading in reference to limit
 P = Peak Reading
 Q = Quasi-peak Reading
 A = Average Reading
 H = Antenna Polarization: Horizontal
 V = Antenna Polarization: Vertical


Calculation Formula

Margin (dB) = Result (dBuV/m) – Limit (dBuV/m)

7.6. TEST RESULTS

Below 1GHz

Model No.	IMB-150D	Test Mode	Mode 1
Environmental Conditions	18°C, 51% RH	6dB Bandwidth	120 kHz
Antenna Pole	Vertical	Antenna Distance	10m
Detector Function	Quasi-peak.	Tested by	David Cheng
Standard	FCC CLASS B W/ CISPR 22 CLASS B LIMIT		




Radiated Emission Readings									
Frequency Range Investigated					30 MHz to 1000 MHz at 10m				
Freq. (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Height (cm)	Degree (°)	Detector (P/Q)	Pol. (H/V)
223.1800	38.60	-15.73	22.87	30.00	-7.13	100	87	Q	V
296.9940	46.00	-12.73	33.27	37.00	-3.73	100	153	Q	V
371.2200	40.20	-10.99	29.21	37.00	-7.79	100	205	Q	V
519.8400	38.50	-6.87	31.63	37.00	-5.37	400	198	Q	V
668.3800	37.10	-4.12	32.98	37.00	-4.02	400	117	Q	V
816.8500	32.40	-1.71	30.69	37.00	-6.31	400	56	Q	V

Note: 1. 30MHz to 1000MHz test is Applicable CISPR 22 standard.

2. P= Peak Reading; Q= Quasi-peak Reading.

Model No.	IMB-150D	Test Mode	Mode 1
Environmental Conditions	26°C, 60% RH	6dB Bandwidth	120 kHz
Antenna Pole	Horizontal	Antenna Distance	10m
Detector Function	Quasi-peak.	Tested by	Kirin Ho
Standard	FCC CLASS B W/ CISPR 22 CLASS B LIMIT		




Radiated Emission Readings									
Frequency Range Investigated					30 MHz to 1000 MHz at 10m				
Freq. (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Height (cm)	Degree (°)	Detector (P/Q)	Pol. (H/V)
150.0000	40.00	-14.47	25.53	30.00	-4.47	400	214	Q	H
258.0000	40.50	-14.48	26.02	37.00	-10.98	400	81	Q	H
279.5000	43.40	-13.00	30.40	37.00	-6.60	400	58	Q	H
462.0000	36.00	-8.12	27.88	37.00	-9.12	100	302	Q	H
494.5000	36.60	-7.30	29.30	37.00	-7.70	100	95	Q	H
602.0000	29.40	-5.77	23.63	37.00	-13.37	100	187	Q	H
770.0000	36.50	-2.54	33.96	37.00	-3.04	100	114	Q	H

Note: 1. 30MHz to 1000MHz test is Applicable CISPR 22 standard.

2. P= Peak Reading; Q= Quasi-peak Reading.

Model No.	IMB-150D	Test Mode	Mode 1
Environmental Conditions	26°C, 60% RH	6dB Bandwidth	120 kHz
Antenna Pole	Vertical	Antenna Distance	10m
Detector Function	Quasi-peak.	Tested by	Kirin Ho
Standard	FCC CLASS B W/ CISPR 22 CLASS B LIMIT + 6dB		




Radiated Emission Readings									
Frequency Range Investigated				30 MHz to 1000 MHz at 10m					
Freq. (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Height (cm)	Degree (°)	Detector (P/Q)	Pol. (H/V)
125.0000	44.00	-13.64	30.36	36.00	-5.64	100	192	Q	V
250.0000	48.10	-14.74	33.36	43.00	-9.64	100	114	Q	V
358.3299	49.60	-11.36	38.24	43.00	-4.76	100	119	Q	V
524.0110	43.10	-6.80	36.30	43.00	-6.70	400	307	Q	V
573.3110	39.50	-6.14	33.36	43.00	-9.64	400	118	Q	V
770.0210	39.00	-2.54	36.46	43.00	-6.54	400	172	Q	V

Note: 1. 30MHz to 1000MHz test is Applicable CISPR 22 standard.

2. P= Peak Reading; Q= Quasi-peak Reading.

Model No.	IMB-150D	Test Mode	Mode 1
Environmental Conditions	26°C, 60% RH	6dB Bandwidth	120 kHz
Antenna Pole	Horizontal	Antenna Distance	10m
Detector Function	Quasi-peak.	Tested by	Kirin Ho
Standard	FCC CLASS B W/ CISPR 22 CLASS B LIMIT + 6dB		



Radiated Emission Readings									
Frequency Range Investigated					30 MHz to 1000 MHz at 10m				
Freq. (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Height (cm)	Degree (°)	Detector (P/Q)	Pol. (H/V)
150.0100	44.50	-14.48	30.02	36.00	-5.98	400	224	Q	H
258.0210	45.00	-14.48	30.52	43.00	-12.48	400	88	Q	H
279.5200	47.90	-12.99	34.91	43.00	-8.09	400	67	Q	H
462.0230	40.80	-8.12	32.68	43.00	-10.32	100	300	Q	H
494.5200	41.50	-7.30	34.20	43.00	-8.80	100	174	Q	H
602.0000	33.50	-5.77	27.73	43.00	-15.27	100	192	Q	H
770.0000	41.50	-2.54	38.96	43.00	-4.04	100	118	Q	H

Note: 1. 30MHz to 1000MHz test is Applicable CISPR 22 standard.

2 P= Peak Reading; Q= Quasi-peak Reading.

Above 1GHz

Model No.	IMB-150D	Test Mode	Mode 1
Environmental Conditions	23°C, 62% RH	6dB Bandwidth	1 MHz
Antenna Pole	Vertical / Horizontal	Antenna Distance	3m
Highest frequency generated or used	2000MHz	Upper frequency	10000MHz
Detector Function	Peak and average.	Tested by	Alee Shen
Standard	FCC CLASS B		

Radiated Emission Readings							
Frequency Range Investigated				Above 1GHz at 3m			
Freq. (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector (P/A)	Pol. (H/V)
1075.000	59.39	-11.26	48.13	74.00	-25.87	P	V
1615.000	47.62	-8.54	39.08	74.00	-34.92	P	V
1815.000	47.96	-7.41	40.55	74.00	-33.45	P	V
2120.000	50.11	-6.00	44.11	74.00	-29.89	P	V
2400.000	47.06	-5.13	41.93	74.00	-32.07	P	V
3080.000	46.66	-2.63	44.03	74.00	-29.97	P	V

Radiated Emission Readings							
Frequency Range Investigated				Above 1GHz at 3m			
Freq. (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector (P/A)	Pol. (H/V)
1075.000	60.17	-11.26	48.91	74.00	-25.09	P	H
1610.000	47.61	-8.57	39.04	74.00	-34.96	P	H
1840.000	48.22	-7.27	40.95	74.00	-33.05	P	H
2125.000	52.10	-5.98	46.12	74.00	-27.88	P	H
2655.000	45.04	-4.21	40.83	74.00	-33.17	P	H
3085.000	46.69	-2.62	44.07	74.00	-29.93	P	H

Note: 1. P= Peak Reading; A= Average Reading.


Model No.	IMB-150D	Test Mode	Mode 1
Environmental Conditions	23°C, 62% RH	6dB Bandwidth	1 MHz
Antenna Pole	Vertical / Horizontal	Antenna Distance	3m
Highest frequency generated or used	2000MHz	Upper frequency	10000MHz
Detector Function	Peak and average.	Tested by	Alee Shen
Standard	FCC CLASS B + 6dB		

Radiated Emission Readings							
Frequency Range Investigated				Above 1GHz at 3m			
Freq. (MHz)	Reading (dBUV)	Factor (dB/m)	Result (dBUV/m)	Limit (dBUV/m)	Margin (dB)	Detector (P/A)	Pol. (H/V)
1075.000	60.73	-11.26	49.47	80.00	-30.53	P	V
1840.000	47.78	-7.27	40.51	80.00	-39.49	P	V
2120.000	49.17	-6.00	43.17	80.00	-36.83	P	V
2400.000	45.96	-5.13	40.83	80.00	-39.17	P	V
2605.000	45.77	-4.41	41.36	80.00	-38.64	P	V
2840.000	45.91	-3.50	42.41	80.00	-37.59	P	V


Radiated Emission Readings							
Frequency Range Investigated				Above 1GHz at 3m			
Freq. (MHz)	Reading (dBUV)	Factor (dB/m)	Result (dBUV/m)	Limit (dBUV/m)	Margin (dB)	Detector (P/A)	Pol. (H/V)
1075.000	60.79	-11.26	49.53	80.00	-30.47	P	H
1615.000	50.52	-8.54	41.98	80.00	-38.02	P	H
1840.000	47.99	-7.27	40.72	80.00	-39.28	P	H
2120.000	50.30	-6.00	44.30	80.00	-35.70	P	H
2400.000	45.72	-5.13	40.59	80.00	-39.41	P	H
3050.000	47.42	-2.72	44.70	80.00	-35.30	P	H

Note: 1. P= Peak Reading; A= Average Reading.

8 PHOTOGRAPHS OF THE TEST CONFIGURATION CONDUCTED EMISSION TEST



RADIATED EMISSION TEST



RADIATED EMISSION TEST (Open Chassis)