

21.5" LCD Open frame IR Touch Monitor (The Water-proof Type)

Model: KOT-0215U-IR3W

Keetouch's 21.5" LCD touch monitors have a long-lasting product cycle because the enclosure is controlled by Keetouch's specifications. Future panel improvements are therefore possible without external changes. The KOT-0215U-IR3W integrate with the Keetouch's IR technology touchscreen.



◆ Features

- Long lasting product cycle-enclosure controlled by Keetouch specifications.
- Future generation panels phased-in without external changes.
- High quality panel with high brightness, high contrast ratio and broad viewing angle.
- Multiple mounting options including rear-mount , VESA mount, horizontal or vertical bracket-mount.
- Keetouch's IR technology on pure glass for the ultimate in image quality.
- USB touch interface.
- Worldwide agency approvals.


Shenzhen K&JAD Technology Co., Ltd

www.keetouch.com

◆ Specifications

Model No.	KOT-0215U-IR3W		
Series	OT		
Structure	Metal-cased Open frame		
LCD Type	Active matrix TFT-LCD	Backlight unit	CCFL
Display Size	21.5" (diagonal)		
Active Area	475.2 mm×267.3 mm		
Suggested Resolution	1920 x 1080 @ 60 Hz		
Support Colors	16.7M		
Brightness(Typ.)	Pure LCD Panel	200cd/m ²	
	With IR Glass Sensor	180cd/m ²	
Response Time(Typ.)	14ms		
Viewing Angle (Typ.at CR>10)	Horizontal(left/right)	89°/89°	
	Vertical(up/down)	89°/89°	
Contrast Ratio(Typ.)	1000:1		
Video Input	Analog RGB		
Video Signal Input Connector	Mini D-Sub 15-pin VGA		
Frequency (H/V)	30~80KHz / 60~75Hz		
Environment	Operating Temp.	0~50°C	
	Storage Temp.	-20~60°C	
	Operating RH:	20%~80%	
	Storage RH:	10%~90%	
Power Supply	Type: External brick Input (line) voltage: 100-240 VAC, 50-60 Hz Output voltage/current: 12 volts at 5 amps max		
MTBF	50,000 Hours		
LCD Back light Life(Typ.)	50,000 Hours		
Weight (N.W/G.W)	7Kg /10Kg (Approx.)		
Power Consumption	35W Max.		
Mount Interface	1)VESA 75mm and 100mm		
	2)Mount bracket, horizontal or vertical		
OSD Control	Buttons	AUTO,+,POWER,-,MENU	
	Function	Brightness, Contrast Ratio, Auto-adjust, Phase, Clock, H/V Location, Languages, Function, Reset	
Touch screen Type	Keetouch 21.5" IR 3MM thickness of touch screen sensor		
Touch System Interface	USB		
Certificates	ETL ,FCC,CE, RoHS		

◆ Mechanical Drawing



◆ Accessories

Power Cable: A North American power cable or an European power cable is included according to the end user's area.

Power Supply Brick: A power supply brick is included.

Touch/Video Cables: USB touch cable, video cable are included

L-brackets: Four standard L-brackets are included.