
22" LCD Open frame SAW Touch Monitor

(the Dust-proof Type with LIP)

User Guide

Rev2.0

Model: [KOT-0220US-SA6BP-LIP1.6](#)



Shenzhen K&JAD Technology Co., Ltd

www.keetouch.com

Dec. 2010

Keetouch's 22" LCD touch monitors have a long-lasting product cycle because the enclosure is controlled by Keetouch's specifications. Future panel improvements are therefore possible without external changes. The KOT-0220US-SA6BP-LIP1.6 integrate with the Keetouch's SAW technology touchscreen.

◆ Features

- Long lasting product cycle-enclosure controlled by Keetouch specifications
- Future generation panels phased-in without external changes
- High quality panel with high brightness,high contrast ratio and broad viewing angle
- Multiple mounting options including rear-mount ,VESA mount, horizontal or vertical bracket-mount
- Keetouch's SAW technology on pure glass for the ultimate in image quality
- Dual USB and RS232 touch interface
- Worldwide agency approvals

Shenzhen KeeTouch Electronic Co., Ltd.

www.keetouch.com

◆ Specification

Model No.	KOT-0220US-SA6BP-LIP1.6	
Series	OT	
Structure	Metal-cased Openframe and ABS Plastic Front Bezel with LIP1.6	
LCD Type	Active matrix TFT-LCD	
Display Size	22 " (diagonal)	
Active Area	473.8 mm×296.1 mm	
Suggested Resolution	1680 x 1050 @ 60 Hz	
Support Colors	16.7M	
Brightness(Typ.)	Pure LCD Panel	300cd/m ²
	With SAW Glass Sensor	275cd/m ²
Response Time(Typ.)	5ms	
Viewing Angle (Typ.at CR>10)	Horizontal(left/right)	85°/85°
	Vertical(up/down)	80°/80°
Contrast Ratio(Typ.)	1000:1	
Video Input	1. Analog RGB 2. DVI	
Video Signal Input Connector	Mini D-Sub 15-pin VGA and DVI-D	